




PV Fluid Products

DIMENSIONAL SUMMARY (Imperial)





MODEL NUMBER	STATORS					ROTORS					
	Overall Length A		Cutback	Tube OD D	Tube ID E	Weight	LENGTH F	HD Length G	HEAD OD H	WEIGHT	Gunbore Diameter
	New (in.)	Min (in.)	inches	inches	inches	pounds	inches	inches	inches	pounds	inches
375435	141	127	6	3.75	3	182	129	5	1.75	77	
475463	207	193	8	4.75	3.75	434	188	6	2.75	208	1
475567	188	174	8	4.75	3.88	352	178	5.5	2.75	219	1
475583	242.6	228.6	8	4.75	3.75	502	229.4	6	2.75	257	1
475726	229.3	215.3	8	4.75	3.75	474	220	5.25	2.75	220	1
475729	250	236	8	4.75	3.75	523	242	5.5	2.99	275	1
475731	238	224	8	4.75	3.75	487	229	6	2.75	316	1
475737	235	221	8	4.75	3.88	562	214.75	6	3.13	297	1
475738	187	173	8	4.75	3.75	393	178	6	2.75	233	1
475750	198	184	8	4.75	3.88	368	186	6	3.13	274	1
500545	122	108	8	5	3.75	317	107	6	2.75	92	1
500660	185	171	8	5	4	411	179.5	6	2.9	240	1
500670	212	198	8	5	4	466	205	6	2.9	273	1
500680	250	236	8	5	4	556	241	6	2.9	321	1
625733	260	246	8	6.25	5	873	252	7	4	740	1
625735	231.25	217.25	8	6.25	5	801	222.25	6	3.5	566	1
625748	203.5	189.5	8	6.25	5	695	194.5	6	3.5	695	1
650545	130	116	8	6.5	5	537	121.5	6	3.5	274	0.75
675470	214.6	200.6	8	6.75	5.5	815	202.5	6	4	520	1
675650	200	186	8	6.75	5.5	775	194	6	4	550	1
675729	220	206	8	6.75	5.5	833	213.5	7	4	609	1
675733	245	231	8	6.75	5.5	912	238.5	7.5	4	663	2
675750	204	190	8	6.75	5.5	758	188	6	4	651	1
675757	260	246	8	6.75	5.5	957	252	7	4.5	866	1
675760	235	221	8	6.75	5.5	875	223	7	4	767	1
675764	245	231	8	6.75	5.5	912	238.5	7	4	820	1



PV Fluid Products

DIMENSIONAL SUMMARY (Imperial)



MODEL NUMBER	STATORS					ROTORS					
	Overall Length A		Cutback	Tube OD D	Tube ID E	Weight	LENGTH F	HD Length G	HEAD OD H	WEIGHT	Gunbore Diameter
	New (in.)	Min (in.)	inches	inches	inches	pounds	inches	inches	inches	pounds	inches
700582	246	232	8	7	5.5	1115	233	7	4.5	641	1
700768	246	232	8	7	5.75	1099	233	7	4.5	788	1
700775	250	236	8	7	5.75	981	241	7	4.5	838	1
800453	228	214	9	8	6.25	1371	221	7	4.75	648	2
800550	168	154	9	8	6.25	1016	162	7	4.75	560	2
800640	206	192	9	8	6.25	1242	199	7	4.75	618	2
800722	228	214	9	8	6.25	1359	221	8	4.75	840	2
800740	206	192	9	8	6.25	1241	196.5	7	4.75	764	2
962650	208	194	9	9.625	7.88	1562	202	7	5.5	1173	2